

**AdVantEdge DWS-2S-2710-02**

The DWS-2S-2710-02 is a dual stage water treatment approach with an integrated system design, ideal for under-counter household use. The system includes two selected 2.75 x 9.75 inch arsenic removal cartridges, housing components, i.e., sumps, caps, mounting bracket, faucet (lead-free), shut-off device, and tubing for a complete unit. AdEdge Technologies, Inc. supplies both the system components and replacement cartridges. The system is available to qualified water treatment distributors and dealers for subsequent re-sale to end users. Replacement cartridges are available through AdVantEdge authorized distributors.



**Specifications**

Arsenic Cartridge  
Materials Housing  
Mounting  
Faucet  
Shut Off Device  
Arsenic media  
Water source  
NSF testing  
Box/Packaging

**Model: DWS-2S-2710-02**

Two 10 inch standard (2.75 x 9.75 inch); AdVantEdge Model AD2710S  
Injection molded polypropelene  
Painted metal mounting bracket  
Lead-free faucet with ¼ inch tubing  
Mechanical countdown shut-off device mounted on bracket  
AdEdge custom AD33L product  
Potable water of known microbiological quality (microbiologically safe)  
Components tested in accordance with NSF protocols, no specific listings  
Plain white box, with or without Label

**Performance**

Rated Cartridge Life                    1000 gallons  
Arsenic concentration                Up to 50 ppb influent arsenic  
Replacement                            Every 12 months or 1000 gallons, whichever comes first  
Rated flow rate                         0.5 gpm  
Parameters                                AD2710S: arsenic

Contact your local dealer: